



STRONG SRT 5000

Super Sensitive Tuner Closed Captions & Teletext

- **Dolby Digital: SPDIF Coaxial**
- **SCART: RGB, CVBS**
- **Super Video Output: 4 Pin Mini Din**
- **RCA/Cinch - CVBS**
- **16:9 Fullscreen, 4:3 Letterbox & Fullscreen**
- **Auto & Manual Search Mode**
- **Favourite Channel List Editing**
- **Fully Adjustable MENU Interface with Picture in Menu**
- **EPG - Electronic Program Guide**
- **Full Function Infra Red Remote Control**
- **Captions & Teletext (Does NOT require Teletext capable TV)**
- **Signal / Quality Level Indicator**
- **Time Clock Setting**
- **6 Timer Event Settings**
- **Sleep Timer**
- **Password Change Option**
- **Integrated Tuner RF Modulator**
- **RS232 Port for Software Upgrade**
- **DVB/T Compliant**
- **COFDM Demodulation**
- **12/24 VDC Power Supply**

DIGITAL TERRESTRIAL TELEVISION RECEIVER



**STRONG** Technologies



SRT 5000 SPECIFICATIONS



TUNER

Guard Internal Modes : 1/32, 1/16, 1/8, 1/4 Active Symbol Duration
FEC Modes Rates : 1/2, 2/3, 3/4, 5/6, 7/8
Input Connector : IEC 169-2, Female
Frequency Range : 51-862MHz
Demodulator : COFDM 2K/8K-Carrier
Channel Bandwidth : 7MHz (for Australia)

MPEG TS A/V Decoder

Video Resolution : 720 x 576
Audio Mode : Single / Dual Channel
Transport Stream : MPEG-2 ISO/IEC 13818-1
Audio Decoding : MPEG/Musical Layer 1 & 2
Input Bit Rate : Max. 90 Mbit/s

RF Modulator

PLL type : Ch 21-69 for selectable Output Channel
RF Connector : 75 Ohms, 162-2, Male/Female - PAL IEC
TV Standard : PAL B/G, I, D/K, NTSC M selectable

A/V & Data Input/Output

Video : RCA/Cinch (CVBS)
: RCA/Cinch Volume & Mute Control
: SCART - RGB, CVBS
: 4 Pin Mini Din Connector - SVHS
Audio : Resolution: 20 bits DAC, Max 2 Vrms
: S/PDIF of Dolby Digital and MPEG-2 Bit Stream Out
RS-232C : Transfer Rate 115Kbps, 9 PIN D-Sub Type

System Resources

Flash Memory : 2Mbyte
SDRAM : 8Mbyte
Main CPU MPEG Chip : STi 5518

Power Supply


Input Voltage : 12/24 VDC Power Supply
Protection : Separate Internal Fuse
Power Consumption : Max. 20 W
Type : SMPS

Physical Specifications

Size (W x H x D) : 280 x 40 x 195 (case) 206 (end of connectors) mm
Net Weight : 1.0 Kg
Operating Temperature : 0 C ~ 50 C

E. & O. E.

DISTRIBUTED BY:



STRONG TECHNOLOGIES PTY LTD. - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA 3803, AUSTRALIA
Phone: +61 3 8795-7990 Fax: +61 3 8795-7991

STRONG & CO. (FAR EAST), LTD. - P.O. BOX: 85 - YOKOHAMA, KANAGAWA-KEN - JAPAN 231-91 - FAX: +81 45 662-4957

www.strong-technologies.com